

IN THE CLAIMS:

Please amend the claims as indicated below.

1. (Previously Presented) A method for transmitting data in a multiple antenna
5 communication system having N transmit antennas, said method comprising the step of:
transmitting a legacy preamble and at least one additional long training symbol on
each of said N transmit antennas, wherein said legacy preamble comprises at least one long
training symbol, wherein a sequence of each of said long training symbols on each of said N
transmit antennas are orthogonal, and wherein each of said long training symbols are time
10 orthogonal by introducing a phase shift between at least two of said training symbols transmitted
on one of said N transmit antennas.
2. (Original) The method of claim 1, wherein said legacy preamble further
comprises at least one short training symbol.
- 15 3. (Original) The method of claim 1, wherein said legacy preamble further
comprises at least one SIGNAL field.
4. (Original) The method of claim 1, wherein said legacy preamble is an 802.11 a/g
20 preamble.
5. (Cancelled)
6. (Cancelled)
- 25 7. (Previously Presented) The method of claim 1, wherein said phase shift is
introduced to each of said long training symbols using a complex rotation.
8. (Original) The method of claim 1, wherein N is two and wherein said transmitting
30 step further comprises the step of transmitting a legacy preamble having at least one long
training symbol and one additional long training symbol on each of said two transmit antennas.

wherein one of said transmit antennas transmits one of said long training symbols with a reversed polarity.

9. (Original) The method of claim 1, whereby a lower order receiver can interpret
5 said transmitted data.

10. (Original) The method of claim 1, further comprising the step of transmitting a
field indicating said number N of transmit antennas.

10 11. (Original) The method of claim 1, further comprising the step of transmitting a
field identifying an employed coding scheme.

12. (Original) The method of claim 1, further comprising the step of transmitting a
field identifying channel bonding options.

15 13. (Original) The method of claim 1, further comprising the step of transmitting a
field identifying a long training symbol format.

14. (Original) The method of claim 1, wherein said legacy preamble has a shorter
20 guard interval.

15. (Original) The method of claim 1, wherein said legacy preamble has a long
training field containing only one long training symbol.

25 16. (Previously Presented) A transmitter in a multiple antenna communication
system, comprising:

a transmitter circuit; and

N transmit antennas for transmitting a legacy preamble and at least one additional
long training symbol on each of said N transmit antennas, wherein said legacy preamble
30 comprises at least one long training symbol, wherein each of said long training symbols are
orthogonal, and wherein each of said long training symbols are time orthogonal by introducing a

phase shift between at least two of said training symbols transmitted on one of said N transmit antennas.

17. (Original) The transmitter of claim 16, wherein said legacy preamble further
5 comprises at least one short training symbol.

18. (Original) The transmitter of claim 16, wherein said legacy preamble further
comprises at least one SIGNAL field.

10 19. (Original) The transmitter of claim 16, wherein said legacy preamble is an 802.11
a/g preamble.

20. (Cancelled)

15 21. (Cancelled)

22. (Previously Presented) The transmitter of claim 16, wherein each of said time
orthogonal long training symbols are stored in memory and said phase shift is introduced when
said long training symbols are transmitted.

20 23. (Original) The transmitter of claim 16, wherein N is two and wherein said
transmitting step further comprises the step of transmitting a legacy preamble having at least one
long training symbol and one additional long training symbol on each of said two transmit
antennas, wherein one of said transmit antennas transmits one of said long training symbols with
25 a reversed polarity.

24. (Original) The transmitter of claim 16, whereby a lower order receiver can
interpret said transmitted data.

30 25. (Original) The transmitter of claim 16, further comprising the step of transmitting
a field indicating said number N of transmit antennas.

26. (Currently Amended) A method for receiving data on at least one receive antenna transmitted by a transmitter having N transmit antennas in a multiple antenna communication system, said method comprising the steps of:

receiving a legacy preamble and at least one additional long training symbol on
5 each of said N transmit antennas, wherein said legacy preamble comprises at least one long training symbol and an indication of a duration of a transmission of said data, wherein a sequence of each of said long training symbols on each of said N transmit antennas are orthogonal, said legacy preamble transmitted such that said indication of a duration is capable of being ~~can be~~ interpreted by a lower order receiver, and wherein each of said long training
10 symbols are time orthogonal due to a phase shift that was introduced between at least two of said training symbols transmitted on one of said N transmit antennas; and
deferring for said indicated duration.

27. (Original) The method of claim 26, wherein said method is performed by a SISO
15 receiver.

28. (Original) The method of claim 26, wherein said indication is transmitted in a SIGNAL field that complies with the 802.11 a/g standards.

29. (Currently Amended) A receiver in a multiple antenna communication system having at least one transmitter having N transmit antennas, comprising:

a receiver circuit; and
at least one receive antenna for receiving a legacy preamble and at least one additional long training symbol on each of said N transmit antennas, wherein said legacy
25 preamble comprises at least one long training symbol and an indication of a duration of a transmission of said data, wherein a sequence of each of said long training symbols on each of said N transmit antennas are orthogonal, said legacy preamble transmitted such that said indication of a duration is capable of being ~~can be~~ interpreted by a lower order receiver, and wherein each of said long training symbols are time orthogonal due to a phase shift that was
30 introduced between at least two of said training symbols transmitted on one of said N transmit antennas; and

means for deferring for said indicated duration.